



HD-CCD Camera



UC-7002SY / UC-7003SY

Specification

| Model | UC-7002SY | UC-7003SY |
|-------------------------|--|--|
| Pick Up Element | 1/3" Sony CCD | |
| Horizontal Resolution | 700TVL | |
| S/N Ratio | More than 48dB | |
| Clock Frequency (MHZ) | NTSC:28.636 , PAL:28.375 | |
| Scanning System | 2:1 interlace | |
| Minimum Illumination | 0 Lux (with IR LED ON) | |
| Synchronous System | Internal, Negative sync. | |
| Auto Electronic Shutter | , NTSC:1/60s~1/100 000s,PAL:1/50s~1/100,000s | |
| Gama Characteristic | 0.45 | |
| IR Distance | 20 Meters (with 24 unit infrared LED) | 30 Meters (with 36 unit infrared LED) |
| IR Power On | CDS Auto Control | |
| Video Output | 1Vpp,75 Ω | |
| Auto Gain Control | Auto | |
| Power/Current | 12VDC(±10%) | |
| Lens | 3.6 mm | 6 mm |
| Water Resistance | IP66 | |
| Storage Temperature | -30~ +60℃ RH95%Max | |
| Operating Temperature | -10~ +50℃ RH95% Max | |