



## IP Camera

### Features:

- 1/2.7" IMX122 super low illumination sensor
- High-performance dual core DSP(Hi3516C)
- H.264 video compression and JPEG image capture
- Max 1~30fps 1080P resolution
- Dual encoding streams supported
- 36 pieces IR LEDs with 25M IR Distance
- Supports Poe
- Support DC12V power supply,
- Built-in Web server, NVR, Onvif protocol approved

## UC-IPC-10801 MP



Model	UC-IPC-10801MP	
<b>General</b>		
Image Sensor	1/2.7" IMX122 super low illumination sensor	
Processor	dual core DSP(Hi3516C)	
Operating System	Embedded RTOS design,dual core DSP(Hi3516C),pure hardware compression,watchdog,	
Resource	Simultaneous remote monitoring, local recording and remote control	
User Interface	WEB, CMS(DSS/ PSS), DMSS, NVR	
Function	Support WEB configuration, OSD, realtime video transmitting, support motion detect and IO alarm activated to remotely recording,screen pop up,message,playback and download,support JPEG capture, support CMS&MYEYE, SDK available	
<b>Camera</b>		
Effective Pixels	1920 (H)×1080(V)	
Electronic Shutter	Auto/Manual, 1/3~1/10000s	Auto/Manual, 1/4~1/10000s
Mini. Illumination	0.1LUX/F1.2(Color), 0.05LUX/F1.2(B/W) 0LUX(IR On)	
Signal Noise Ratio	>50dB	
Gain Control	Auto/Manual	
White Balance	Auto/Manual	
Day/Night	ICR	
Lens Mount	M12	
Lens	3.6mm	
IR Led	<b>36pieces</b>	
Max. IR Distance	<b>25m</b>	
IR Cut	With IR Cut	
<b>Video</b>		
Video Compression	H.264/MJPEG	
Image Resolution	1080P(1920×1080) Sub stream:704*576	
Encoding Speed	1080P(1~30fps)	
Bit Rate	0.1M~6Mbps	
Snapshot	Fastest 1fps JPEG capture	
<b>Network</b>		
Ethernet	RJ-45 (10/100Base-T)	
Network Functions	1xRJ45,10/100M,support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP	
Remote Operation	Monitor, PTZ control, Playback, System setting, File download, Log information, Maintenance & Upgrade	
Mobile Monitor	Support iPhone, Windows Mobile, BlackBerry, Symbian, Android	
<b>Environmental</b>		
Power Supply	DC12V,	
Housing of Material	plastic	
Ingress Protection	4000V thunder, surge and wave protection	
Power Consumption	Max.4W	
Operating Environment	-10℃~-+50℃, 10%~90%	
Dimension	<b>130mm x100mm</b>	
Weight	0.35kg	