



IP Camera

Features:

- 1/2.7" IMX122 super low illumination sensor
- High-performance dual core DSP(Hi3516C)
- H.264 video compression and JPEG image capture
- Max 1~30fps 1080P resolution
- Dual encoding streams supported
- Dual encoding streams supported
- With IR Cut
- Supports Poe
- Support DC12V power supply
- IP66 Water-proof Built-in Web server, NVR, Onvif protocol approved

Model No : UC-IPC10800MP



Model	UC-IPC-10800MP	
General		
Image Sensor	1/2.7" IMX122 super low illumination sensor	
Processor	dual core DSP(Hi3516C)	
Operating System	Embedded RTOS design,dual core DSP(Hi3516C),pure hardware compression,watchdog,	
Resource	Simultaneous remote monitoring, local recording and remote control	
User Interface	WEB, CMS(DSS/ PSS), DMSS, NVR	
Function	Support WEB configuration, OSD, realtime video transmitting, support motion detect and IO alarm activated to remotely recording,screen pop up,message,playback and download,support JPEG capture, support CMS&MYEYE, SDK available	
Camera		
Effective Pixels	1920 (H)×1080(V)	
Electronic Shutter	Auto/Manual, 1/3~1/10000s	Auto/Manual, 1/4~1/10000s
Mini. Illumination	0.1LUX/F1.2(Color), 0.05LUX/F1.2(B/W) 0LUX(IR On)	
Signal Noise Ratio	>50Db	
Gain Control	Auto/Manual	
White Balance	Auto/Manual	
Day/Night	ICR	
Lens Mount	M12	
Lens	Optional	
IR Led	Without	
Video		
Video Compression	H.264/MJPEG	
Image Resolution	1080P(1920×1080) Sub stream:704*576	
Encoding Speed	1080P(1~30fps)	
Bit Rate	0.1M~6Mbps	
Snapshot	Fastest 1fps JPEG capture	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Network Functions	1xRJ45,10/100M,support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP	
Remote Operation	Monitor, PTZ control, Playback, System setting, File download, Log information, Maintenance & Upgrade	
Mobile Monitor	Support iPhone, Windows Mobile, BlackBerry, Symbian, Android	
Environmental		
Power Supply	DC12V,	
Housing of Material	Metal	
Operating Environment	-10℃~+50℃, 10%~90%	
Dimension	155mm x65mm x60mm	
Weight	0.39kg	