



## Indoor speed dome Cameras



### UC-H2110 10X High Speed Dome Camera

#### SPECIFICATIONS

|                                |                                                                   |
|--------------------------------|-------------------------------------------------------------------|
| MODEL                          | UC H2110                                                          |
| Image Sensor :                 | 1/4" SONY CCD                                                     |
| Signal System :                | PAL / NTSC                                                        |
| Effective Pixels:              | 752(H)x582(V); NTSC: 768(H)x494(V)"                               |
| Horizontal Resolution :        | 540TVL                                                            |
| S/N Ratio :                    | ≥48db                                                             |
| White Balance :                | automatic, manual                                                 |
| Build -In-Lens :               | 10X optical zoom                                                  |
| Shutter Speed :                | 1/1—1/10,000s                                                     |
| Minimum Illumination :         | 0.05lux                                                           |
| Gain:                          | Auto / manual override                                            |
| Exposure :                     | Auto , Manual , Shutter , aperture                                |
| Back Light Compensation :      | low / medium / high / off                                         |
| Zoom mode :                    | Auto, Manual, key, interval                                       |
| Video Out :                    | 1.0Vp-p, 75Ω(BNC)                                                 |
| Horizontal range :             | 360 ° unlimited rotation, call the preset position 200 ° / sec    |
| Vertical range :               | 0-90 °                                                            |
| Horizontal of Rotation speed : | Horizontal speed 0.1-220 ° / sec, vertical speed: 0.1-100 ° / sec |
| automatically flip :           | YES                                                               |
| Scan type :                    | support (preset, pattern scan, A-B scan, cruise scan)             |
| communication protocol :       | PELCO_D, PELCO_P                                                  |
| preset number :                | 128                                                               |
| Baud Rate :                    | 19200bps, 9600bps, 4800bps, 2400bps, 1200bps                      |
| communication interface :      | RS485 control                                                     |
| temperature :                  | -20 ° - 65 °                                                      |
| Power :                        | DC12V/2A □ 20W                                                    |
| weight:                        | 2.2kg                                                             |