



Out door speed dome Cameras

UC-H2127 (OSD) 27X PTZ Camera
UC-H2136 (OSD) 36X PTZ Camera
With OSD AND PARKING Function



SPECIFICATIONS

MODEL	UC H2127	UC-H2136
Image Sensor :	1/4"SONY CCD	
Signal System :	PAL	
Effective Pixels:	PAL: 752(H)x582(V)	
Horizontal Resolution :	600 TVL	
S/N Ratio :	≥48db	
White Balance :	automatic, manual	
Build -In-Lens :	27X optical zoom	36X optical zoom
Shutter Speed :	1/1—1/10,000s	
Minimum Illumination :	0.05lux	
Gain:	Auto / manual override	
Exposal :	Auto , Manual , Shutter , aperture	
Back Light Compensation :	low / medium / high / off	
Zoom mode :	Auto, Manual, Zoom trigger, key, interval, trigger	
Video Out :	1.0Vp-p,75Ω(BNC)	
Horizontal range :	360° unlimited rotation, call the preset position 200° / sec	
Vertical range :	0-90 °	
Horizontal of Rotation speed :	Horizontal speed 0.1-220° / sec, vertical speed: 0.1-100 ° / sec	
automatically flip :	YES	
Scan type :	support (preset, pattern scan, A-B scan, cruise scan)	
communication protocol :	PELCO_D, PELCO_P	
preset number :	256	
Baud Rate :	19200bps, 9600bps, 4800bps, 2400bps, 1200bps	
communication interface :	RS485 control	
temperature :	-20 ° - 65 °	
Power :	DC12V/2A 20W	
weight:	4.5kg	