



## DVR Stand alone

### Product Features :

1. The latest H. 264 compression
2. Support 4 channels playback on PC.
3. Support digital zoom function in playback and live view
4. Support USB DVD RW, and 3G module
5. Supports complex streaming encode, recording, playback, net transfer, backup, wireless monitor and DVR running simultaneously.
6. Supports mobile phone monitoring function (iphone / Blackberry / Android / Windows Mobile / symbian Os are available)
7. Supports TCP/IP protocol groups and PPPOE, DHCP, DNS, DDNS, SMTP, NFS, etc
8. Supports 4CH/8CH/16CH playback simultaneously.
9. Supports client software for DVR groups management
10. Supports SDK develop files under Windows OS



## 71 Series 7104/7108/7116

- 3G Data Card Support
- Built in DDNS Server
- HDMI Output
- P2P
- QR-Code

### SPECIFICATIONS

| Model                 | Model                 | 7104XC                                            | 7108XC         | 7116XC            |
|-----------------------|-----------------------|---------------------------------------------------|----------------|-------------------|
| System                | User Interface        | Graphic User interface (OSD Menu)                 |                |                   |
| Video                 | Video Input           | 4 channels                                        | 8 channels     | 16 channels       |
|                       | Video Output          | CVBS, VGA, HDMI                                   |                |                   |
|                       | VGA                   | 1024x768, 1280x720, 1280x1024, 1440x900, 1366x768 |                |                   |
|                       | Display               | 1/4 optional                                      | 1/4/9 optional | 1/4/9/16 optional |
|                       | Video standard        | PAL / NTSC                                        |                |                   |
| Audio                 | Audio inout           | 1 in, 1 out                                       |                | 2 in, 1 out       |
| Recording & Storage   | Audio Compress        | ADPCM                                             |                |                   |
|                       | Video Compress        | H264                                              |                |                   |
|                       | Image quality         | CIF/HD/DI/Optional                                |                | CIF               |
|                       | Audio Stream Standard | ADPCM                                             |                |                   |
|                       | Video Compression     | H.264 VBR/CBR                                     |                |                   |
|                       | Resolution            | CIF/HD1/D1/ (Optional)                            |                |                   |
|                       |                       | CIF : 384 768 Kbps (Optional)                     |                |                   |
|                       | Video Bit Rate        | HDI : 512 - 1024 Kbpal (Optional)                 |                |                   |
|                       |                       | DI - 896 - 1280 Kbps (Optional)                   |                |                   |
| Other                 | Audio Bit Rate        | 32Kbps                                            |                |                   |
|                       | Storage               | 1x2TB                                             |                |                   |
|                       | RS485                 | 1                                                 |                |                   |
| Operation temperature | Ethernet              | 10M / 100M                                        |                |                   |
|                       |                       |                                                   |                |                   |
|                       |                       | -10C 55C                                          |                |                   |
| Operation humidity    |                       |                                                   |                |                   |
|                       |                       | 10%-90%                                           |                |                   |
| Dimension (mm)        |                       | 315(L)X230(W)X45mm                                |                |                   |
| Power input           |                       | DC 12V/2A                                         |                |                   |
| Weights               |                       | 2.5 KG                                            |                |                   |