



DVR Stand alone

UC-9204ST / UC-9208ST / UC-9416ST

SPECIFICATIONS



MODEL NO	UC-9204ST		UC-9208ST	UC-9416ST
System	Compression	Standard H.264		
	CPU	Cortex A9		
	OS	Embedded Linux		
Video	Input	BNC x 4	BNC x 8	BNC x 16
	Output	BNC x 1, VGA x 1:1920x1080, HDMI x 1:1920x1080		
Audio	Input	RCA x 2		
	Output	RCA x 1		
	2-way audio	Take up 1CH audio input		
Record	Resolution	704*576/352*288(PAL) , 704*480/352*240(NTSC)		
	Frame Rate	100fps(PAL)/120fps(NTSC)	125/200fps(PAL)/ 150/240fps(NTSC)	100/400fps(PAL)/ 120/480fps(NTS)
	Bit Rate	128K~2Mbps		
	Encode	VBR/CBR		
	Quality	5 Level		
	Mode	Manual, Timer, Motion		
	File Manager	Lock, unlock, reserving time, redundancy		
Play back	Playback	4CH	8CH	16CH
	Search	Time/calendar search, event (motion)		
	Smart Search	Apply different colors to display whether a channel in a period of time recording or not		
	Function	Play, Pause, FF, FB; Digital zoom		
Alarm	Mode	Motion, Video Loss		
	Input	NO		
	Output	NO		
	Triggering	Record, PTZ move, e-mail, etc		
Network	Interface	RJ45		
	Protocol	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS, E-mail		
	Others	10 users online, dual stream		
Cell Phone	OS	Iphone, Blackberry, Andriod, Windows phone, Symbian		
	Function	Multi-screen surveillance(for certain model), record, snapshot, PTZ control, save the device list		
Port	HDD	SATA x 1, support 2T per HDD		
	RS485	RS485 x1, support PTZ and keyboard		
	USB	USB2.0 x 2, one for mouse, another for USB backup device		
	Remote Controller	1 Optional		
Others	Power Supply	DC: 12V		
	Dimensions	300mm * 270mm * 58mm (W * D * H)		
	Working Environment	0~50 °C, 10%~90% Humidity		