



DVR Stand alone

- 3G Data Card Support
- Built in DDNS Server
- HDMI Output



UC-DN8016 HF

SPECIFICATIONS

SPECIFICATIONS	UC-DN8004 HF	UC-DN8008 HF	UC-DN8016 HF
Video Compression format	H.264		
Language	Multi-languages		
Video System	NTSC	PAL	
Video Input	4 CH	8CH	16CH
Video Outputs	1CH monitor output, VGA output(1280*1024) HDMI		
Video Resolution	704* 480	704* 576	
Display Modes	Full screen, multiple screens, Sequence display, exchangeable channel display, picture-in-picture		
Audio Input	1	1	4
Audio Output	-8Db3kΩ,RCA connector×1		
Recording Modes	Manual, Continue, alarm, motion detection		
Operating System	Embedded Linux		
Operating Method	USB mouse, remote control, control panel		
Multiplex Operation	live & record & playback & backup & network		
Emergency Play Back	Yes		
Frame and Resolution	CIF:PAL 100fps/352*288	CIF:PAL 200fps/352*288	
	1/2D1:PAL 100fps/704*288	1/2D1:PAL 200fps/704*288	
	D1:PAL 50fps/704*576	D1:PAL 100fps/704*576	
Watchdog (LED indicator)	Power, channel, backup, network		
Event Modes	Alarm trigger, motion detection trigger		
High Playback Speed	2, 4, 6,8 ,16 multiplier , single frame playback		
Playback Searching	Date & time search, event list search, urgent search		
Playback Modes	Support 4CH playback simultaneously	Support 8CH playback simultaneously	Support 16CH playback simultaneously
Network Protocols	TCP/IP, DHCP&PPPOE & DDNS		
Network Port	10M/100M Ethernet port		
Mobile monitoring	Windows mobile, Symbian, iphone, Blackberry, Android		
Confidential Function	User and administrator Password Protection		
PTZ Control	RS485		
HDD Port	Support 2 SATA hard disk		
HDD Occupation Space	All 4 channels record at high quality mode:1GB/H		
Backup System	USB, network backup		
Power Supply	DC: 12V/3A		
Power consumption(No HDD)	20W		
Dimensions	330(L)* 245(W)* 60(H) mm	330(L)* 245(W)* 60(H) mm	
Weight	3.2kg (No HDD)	3.0KG(No HDD)	
Environment	Operating Temperature: +5°~ +50° Storage Temperature: -20°~ +70° Humidity: 30 ~95%		